

2KW DVB-T Transmitter VHF/UHF



Features:

- All solid-state digital TV transmitter, bandwidth is 6-8MHZ.
- Pre-distortion correction, dual-excitters switch automatically.
- High Linearity LDMOS Power Amplifier, high-gain power amplifier module, parallel switching power supply, it is a high-efficiency transmitter.
- Telemetry and remote control by computer, web-based interface and software.
- Good man-machine interface, full automatic switch the machine with one key.
- Multi protection (over voltage, over current, overheating, large standing-wave ratio ...)high reliability, 24 hours continuous works.

Technical Specifications:

1. Working frequency: VHF/UHF
2. Channel bandwidth: 8MHz
3. Output power: 2KW
4. Output impedance: 50Ω
5. Output interface: Φ40
6. Output load return loss: Normal operation: -32dB
Allowed operation: -20dB
7. Power input level: 0dBm
8. Amplifier input impedance: 50Ω
9. Amplifier input interface: L16

- 10. Useless transmission: $\leq -60\text{dB}$
- 11. Band fluctuations: $\pm 0.5\text{dB}$
- 12. Band shoulder: better than 36dB
- 13. MER: better than 30dB
- 14. Size: $1840\text{mm} \times 1160\text{mm} \times 870\text{mm}$
- 15. Weight: 500KG